

Better than it has to be[®] Since 1903

HYPOID GEAR GL-5 LUBRICANI

BENEFITS:

- » Excellent EP and Anti-Wear Properties
- » Strong Resistance to Oxidation
- » Protects Against Rust and Corrosion
- » Excellent Demulsibility
- » Compatibility with Seal Materials



SAE

80W-90







AMALIE Hypoid Gear Multi-Purpose GL-5 80W-90 Gear Oil is a premium gear lubricant designed for both light and heavy-duty commercial axles, and final drives. Features include excellent thermal and oxidation stability, compatibility with seal materials, water separation, foam suppression, and superior storage stability.

Check owner's manual for specific recommendations.

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Viscosity Grade	80W-90
Kinematic Viscosity @100°C, cSt	
Kinematic Viscosity @40°C, cSt	
Viscosity Index	105
Flash Point, °C (°F)	240 (464)
Pour Point, °C (°F)	30 (-22)
Density, S.G	0.89
Brookfield Viscosity, -26°C, cP	
Typical values are listed. Variations not affecting the performance of this fluid may occur du production: however, these variations will not fall outside of set specification parameters.	ring

Please consult AMALIE Technical Services or your local representative for a full listing of applications.

Technical Services: • (800) 368-1264 • techservices@amalie.com

HYPOID GEAR LUBE MP

VISCOSITY	PACK SIZE	PART #
80W-90	12-1 Quart	160-73126-56
	4-1 Gallon	160-73127-36
	5 Gallon Pail	160-73124-25
	16 Gallon Keg	160-73120-16
	55 Gallon Drum	160-73123-05

The data presented herein are believed to be accurate; however, Amalie Oil Company shall not be liable for its content and makes no warranty with respect thereto.

Health and Safety

Safety Data Sheets (SDS) are available from your sales representative or at AMALIE.com.

RECOMMENDATIONS

AMALIE Hypoid Gear Multi-Purpose GL-5 80W-90 Gear Oil is recommended for gear boxes and transaxles that call for GL-5 gear oil.