

# LIMITED SLIP

## MP HYPOID GEAR LUBRICANT

80W-90

API: GL-5

### **BENEFITS:**

- » Excellent EP and Anti-Wear Properties
- » Strong Resistance to Oxidation
- » Protects Against Rust and Corrosion
- » Excellent Water Handling Characteristics
- Compatibility with Seal Materials







AMALIE Limited Slip MP Hypoid LS GL-5 80W-90 Gear Oil meets the API GL-5 hypoid gear performance classification, and the features listed for hypoid gear multipurpose plus it contains limited-slip (LS) chemistry to prevent/reduce differential chatter as well as being formulated from the highest quality base oils and a new and improved GL-5 additive system.

Check owner's manual for specific recommendations.

#### TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Viscosity Grade	80W-90
Kinematic Viscosity @100°C, cSt	15.0
Kinematic Viscosity @40°C, cSt	145
Viscosity Index	105
Flash Point, °C (°F)	250 (482)
Pour Point, °C (°F)	30 (-22)
Density, S.G	0.893
Brookfield Viscosity, -26°C, cP	<100,000

Typical values are listed. Variations not affecting the performance of this fluid may occur during production; however, these variations will not fall outside of set specification parameters.

Please consult AMALIE Technical Services or your local representative for a full listing of applications.

Technical Services: • (800) 368-1264 • techservices@amalie.com

#### MP HYPOID GEAR LUBE LIMITED SLIP

VISCOSITY	PACK SIZE	PART#
80W-90	12-1 Quart	160-73026-56
	5 Gallon Pail	160-73024-25
	16 Gallon Keg	160-73020-16
	55 Gallon Drum	160-73023-05

The data presented herein are believed to be accurate; however, Amalie Oil Company shall not be liable for its content and makes no warranty with respect thereto.

#### **Health and Safety**

Safety Data Sheets (SDS) are available from your sales representative or at AMALIE.com.

#### RECOMMENDATIONS

AMALIE Limited Slip MP Hypoid LS GL-5 80W-90 Gear Oil is recommended for gear boxes and transaxles that call for GL-5 gear oil.