

Better than it has to be[®] Since 1903



sae 250



API GL-1

BENEFITS:

- » Protects Against Rust & Corrosion
- » Good Film Strength
- » Good Yellow Metal Protection
- » Strong Resistance to Oxidation









AMALIE SMG Gear Lube GL-1 SAE 250 Gear Oil is a high quality straight mineral gear oil formulated to meet the API GL-1 performance classification and to satisfy the basic gear oil demands of many high-performance over-the-road transmissions as well as many older transmission units.

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

| SAE Grade | 250 |
|---------------------------------|-----------|
| API Gravity | 24 |
| Kinematic Viscosity @100°C, cSt | 43 |
| Viscosity Index | 100 |
| Pour Point, °C (°F) | 12 (10) |
| Flash Point, °C (°F) | 240 (464) |

Typical values are listed. Variations not affecting the performance of this fluid may occur during production; however, these variations will not fall outside of set specification parameters.

RECOMMENDATIONS

AMALIE SMG Gear Lube GL-1 SAE 250 Gear Oil is recommended for many types of automotive and industrial applications where the use of a straight-weight mineral gear oil is recommended.

Please consult AMALIE Technical Services or your local representative for a full listing of applications.

Technical Services: • (800) 368-1264 • techservices@amalie.com

SMG GEAR LUBE

| VISCOSITY | PACK SIZE | PART # |
|-----------|----------------|--------------|
| GL-1 250 | 5 Gallon Pail | 160-62934-25 |
| | 55 Gallon Drum | 160-62933-05 |

Always refer to your vehicles operating manual to select the correct grade of oil for your engine. The data presented herein are believed to be accurate; however, Amalie Oil Company shall not be liable for its content and makes no warranty with respect thereto.

Health and Safety

Safety Data Sheets (SDS) are available from your sales representative or at AMALIE.com.