

**AMALIE**<sup>®</sup>

Better than it has to be<sup>®</sup>  
Since 1903



# 2T MOTORCYCLE OIL

## BENEFITS:

- » Excellent Miscibility
- » Cost Effective



**MADE IN U.S.A.**



Better than it has to be<sup>®</sup>  
Since 1903



**AMALIE 2T Motorcycle Oil** is designed for 2-cycle engine application and for every budget. It may be used in either pre-mix or mix-on-demand VRO oil delivery systems. **AMALIE 2T Motorcycle Oil** delivers excellent service up to a 100:1 fuel-to-oil ratio for individual engines. Always consult the owner’s manual for the recommended engine oil type and for the specific fuel-to-oil mix ratios.

Always consult your vehicle’s owner’s manual when selecting the appropriate viscosity and service grade.

## TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Viscosity Grade.....	SAE 30
Kinematic Viscosity @100°C, cSt.....	10.0
Kinematic Viscosity @40°C, cSt.....	82.9
Viscosity Index.....	100
Sulfated Ash, Mass %.....	0
Flash Point, °C (°F).....	220 (428)
Visual Color.....	Blue
API Gravity.....	30.9

Typical values are listed. Variations not affecting the performance of this fluid may occur during production; however, these variations will not fall outside of set specification parameters.

Always refer to your vehicles operating manual to select the correct grade of oil for your engine. The data presented herein are believed to be accurate; however, Amalie Oil Company shall not be liable for its content and makes no warranty with respect thereto.

Please consult AMALIE Technical Services or your local representative for a full listing of applications.

Technical Services:  
(800) 368-1264  
techservices@amalie.com

### Health and Safety

Safety Data Sheets (SDS) are available from your sales representative or at AMALIE.com.

### 2T MOTORCYCLE OIL

VISCOSITY	PACK SIZE	PART #
30	12-1 Quart	160-62766-56
	55 Gallon Drum	160-62763-05