

# AMALIE®

Better than it has to be®  
Since 1903



## 2T

# Synplus™

SYNTHETIC BLEND TECHNOLOGY

MOTORCYCLE OIL

API: TC, ISO-L-EGC, EGD  
and JASO FC, FD.

SAE  
20W-20

### BENEFITS:

- » Formulated with a Blend of Premium Synthetic and Conventional Base Stocks
- » Low-Ash Chemistry
- » Smoke Reducing Additives Protect the Environment
- » Protects Against Wear and Corrosion



MADE IN U.S.A.



Better than it has to be®  
Since 1903



**AMALIE Synplus Synthetic Blend 2T SAE 20W-20 Motorcycle Oil** is a synthetic blend lubricant formulated for high performance air-cooled 2-cycle motorcycle engines. It protects against high-temperature oxidation and corrosion while also ensuring cleanliness. This is a low ash formulation that prevents carbon deposit build-up on engine parts, and protects against ring sticking. This oil is formulated with high-temperature performance chemistry and special smoke reducing components to give you the ultimate in engine protection and environmental performance. These oils may be used in other air-cooled applications, such as snowmobiles, lawn mowers, string trimmers, air-blowers, snow blowers, all-terrain vehicles and many others requiring API service category TC, ISO-L-EGC, EGD and JASO FC, FD.

Always consult your vehicle's owner's manual when selecting the appropriate viscosity and service grade.

## TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Viscosity Grade.....	SAE 20W-20
Kinematic Viscosity @100°C, cSt.....	7.0
Kinematic Viscosity @40°C, cSt.....	42.0
Viscosity Index.....	135
Sulfated Ash, Mass %.....	0.08
Flash Point, °C (°F).....	200 (392)
Pour Point, °C (°F).....	-24 (-11.2)
Visual Color.....	Red
API Gravity.....	32.5

Typical values are listed. Variations not affecting the performance of this fluid may occur during production; however, these variations will not fall outside of set specification parameters.

Always refer to your vehicles operating manual to select the correct grade of oil for your engine. The data presented herein are believed to be accurate; however, Amalie Oil Company shall not be liable for its content and makes no warranty with respect thereto.

Please consult AMALIE Technical Services or your local representative for a full listing of applications.

Technical Services:  
(800) 368-1264  
techservices@amalie.com

### Health and Safety

Safety Data Sheets (SDS) are available from your sales representative or at AMALIE.com.

### 2T SYNPLUS SYNTHETIC BL MOTORCYCLE OIL

VISCOSITY	PACK SIZE	PART #
20W-20	12-1 Quart	160-62796-56
	55 Gallon Drum	160-62793-05