

# AMALIE

Better than it has to be<sup>®</sup>  
Since 1903

## X-TREME 4T

# MOTORCYCLE OIL



## SAE 10W-40

API: SG, JASO MA

### BENEFITS:

- » Outstanding Thermal and Oxidation Stability
- » Excellent Sludge and Varnish Protection
- » Volatility: Lowers Oil Vaporization and Consumption at Extreme Conditions
- » Excellent Wear Protection
- » Outstanding Frictional Characteristics



MADE IN U.S.A.



Better than it has to be®  
Since 1903

# X-TREME 4T

## MOTORCYCLE OIL

**AMALIE 4T X-Treme Max Motorcycle Oil 10W-40** is designed to provide wear protection, sludge and varnish protection, and thermal stability for superior performance in four-cycle motorcycle applications. Blended with high-quality base stocks and performance chemistry; the **AMALIE 4T X-Treme Max Motorcycle Oil 10W-40** is formulated for superior operation in high-revving, high-temperature motorcycle engines and is blended to give superior performance in those engines and transmissions that have a common sump and require specialized frictional characteristics for clutches and wet brakes.. The **AMALIE 4T X-Treme Max Motorcycle Oil 10W-40** meets or exceeds the API SG and JASO MA categories.

Always consult your vehicle's owner's manual when selecting the appropriate viscosity and service grade.

### TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Viscosity Grade.....	SAE 10W-40
Kinematic Viscosity @100°C, cSt.....	13.5
Kinematic Viscosity @40°C, cSt.....	91.65
Viscosity Index.....	150
Cold Cranking Viscosity, cP @ -25 (°C) .....	5500
Flash Point, °C (°F).....	220 (428)
Pour Point, °C (°F).....	-33 (-27.4)
HT/HS Viscosity, cP.....	3.7
TBN, mgKOH/gram .....	5.0

Typical values are listed. Variations not affecting the performance of this fluid may occur during production; however, these variations will not fall outside of set specification parameters.

Always refer to your vehicles operating manual to select the correct grade of oil for your engine. The data presented herein are believed to be accurate; however, Amalie Oil Company shall not be liable for its content and makes no warranty with respect thereto.

Please consult AMALIE Technical Services or your local representative for a full listing of applications.

Technical Services:  
(800) 368-1264  
techservices@amalie.com

#### Health and Safety

Safety Data Sheets (SDS) are available from your sales representative or at AMALIE.com.

#### X-TREME 4T MOTORCYCLE OIL

VISCOSITY	PACK SIZE	PART #
10W-40	12-1 Quart	160-72676-56