

AMALIE

Better than it has to be[®]
Since 1903



EliteXir

FULL SYNTHETIC

SAE 5W-50

ATV/UTV MOTOR OIL

BENEFITS:

- » Excellent Wear Protection
- » Outstanding Resistance to Mechanical Shear at High Temperatures and High Loads
- » Increased Resistance to Oxidative Breakdown
- » Ideal Wet Clutch Performance
- » Peak Horsepower Gains



MADE IN U.S.A.



Better than it has to be[®]
Since 1903



FULL SYNTHETIC
ATV/UTV

AMALIE Elixir 4T ATV / UTV Oil 5W-50 is designed and tested specifically for the demands of ATV or UTV vehicles. Formulated with synthetic base stocks and a proprietary mixture of additive chemistries; it is designed to offer maximum engine and clutch protection to your power sports equipment. **AMALIE Elixir 4T ATV / UTV Oil 5W-50** does not contain friction modifier. It promotes smooth shifting and positive clutch engagement. It will protect your high-revving engine from wear and is designed to remove heat from the lubricating systems quickly and efficiently.

AMALIE Elixir 4T ATV / UTV Oil 5W-50 is designed to provide excellent protection at start-up even in sub-zero weather. Its inherent shear stability resists thinning at high-temperatures. **AMALIE Elixir 4T ATV / UTV Oil 5W-50** provides all-season performance and eliminates the need to use different viscosity oils depending upon ambient temperatures.

Always consult your vehicle's owner's manual when selecting the appropriate viscosity and service grade.

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Kinematic Viscosity @100°C, cSt.....	18.5
Kinematic Viscosity @40°C, cSt.....	84.0
Viscosity Index.....	185
Color.....	Amber 3.0
Specific Gravity.....	0.85
Flash Point, °C.....	220
Pour Point, °C.....	-51
Noack Volatility, %Loss.....	7.5
High Temperature High Shear (HTHS), cP.....	5.2

Typical values are listed. Variations not affecting the performance of this fluid may occur during production; however, these variations will not fall outside of set specification parameters.

Please consult AMALIE Technical Services or your local representative for a full listing of applications.

Technical Services: • (800) 368-1264 • techservices@amalie.com

ELIXIR FULL SYNTHETIC ATV / UTV OIL

VISCOSITY	PACK SIZE	PART #
5W-50	12-1 Quart	160-72516-56

Always refer to your vehicles operating manual to select the correct grade of oil for your engine. The data presented herein are believed to be accurate; however, Amalie Oil Company shall not be liable for its content and makes no warranty with respect thereto.

Health and Safety

Safety Data Sheets (SDS) are available from your sales representative or at AMALIE.com.

APPLICATIONS

AMALIE Elixir 4T ATV / UTV Oil 5W-50 exceeds API SM requirements and is recommended for applications requiring JASO MA or MA 2 performance. For use in all ATV/UTV applications requiring the use of 5W-50 engine oil. Please contact your Sales Representative for a full listing of OEM specific applications.

Additional Information

Please use proper handling and care that you would use with any motor oil. Contact your Sales Representative for SDS.