

AMALIE®

Better than it has to be®
Since 1903



FORM OIL 70

ISO
15

BENEFITS:

- » No Discoloration
- » Excellent Release Properties
- » Smooth Finish



MADE IN U.S.A.



Better than it has to be[®]
Since 1903

FORM OIL 70

AMALIE Form Oil 70 is designed to function as a concrete form release oil. It is formulated from lightly colored mineral base stocks to deter discoloration. It may be used with either wood or metal forms.

AMALIE Form Oil 70 may be applied by either brushing or spraying.

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Viscosity Grade.....	ISO 15
Kinematic Viscosity @ 100°C, cSt.....	3.4
Kinematic Viscosity @ 40°C, cSt.....	15.0
Viscosity Index.....	100
Flash Point, °C.....	180 (356)
Pour Point, °C.....	-27 (-16.6)
Density, S.G.....	0.855

Typical values are listed. Variations not affecting the performance of this fluid may occur during production; however, these variations will not fall outside of set specification parameters.

Please consult AMALIE Technical Services or your local representative for a full listing of applications.

Technical Services: • (800) 368-1264 • techservices@amalie.com

FORM OIL 70

VISCOSITY	PACK SIZE	PART #
ISO 15	55 Gallon Drum	160-67673-05

Health and Safety

Safety Data Sheets (SDS) are available from your sales representative or at AMALIE.com.

The data presented herein are believed to be accurate; however, Amalie Oil Company shall not be liable for its content and makes no warranty with respect thereto.