

AMALIE®

Better than it has to be®
Since 1903



PRO TWO-CYCLE

TC-W3® RL

ENGINE OIL

BENEFITS:

- » Ash-less
- » Clean Burning
- » Low Smoke



NMMA certified for TC-W3® RL at the engine manufacturer's recommended fuel/oil ratio.



MADE IN U.S.A.



Better than it has to be[®]
Since 1903



AMALIE Pro Two-Cycle TC-W3[®]RL Engine Oil provides the highest level of protection for high performance, high horsepower, two-cycle marine engines. This oil is certified NMMA (BIA) and it is formulated to combat wear, scuffing and deposits. It is a high-temperature oxidation resistant oil which protects against corrosion, ensures cleanliness, and provides lubricity for long engine life. This is an ash-less formulation that prevents carbon deposit build-up on engine parts and protects against ring sticking. **AMALIE Pro Two-Cycle TC-W3[®]RL Engine Oil** oil is recommended for all water cooled two-cycle engines, including the performance demands of Mercury, OMC Johnson/Evinrude, Yamaha, Honda, Kawasaki and many other engines requiring NMMA TC-W 3, TC-W 2, or TC-W type oils. These oils may be used in other air-cooled and water-cooled applications, such as snowmobiles, personal watercraft (PWC), jet skis, lawn mowers, snow blowers, all-terrain vehicles and many others requiring API service category TC.

Always consult your vehicle's owner's manual when selecting the appropriate viscosity and service grade.

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Viscosity Grade.....	SAE 20
Kinematic Viscosity @100°C, cSt.....	8.1
Kinematic Viscosity @40°C, cSt.....	52
Viscosity Index.....	125
Sulfated Ash, Mass %.....	0
Flash Point, °C (°F).....	190 (374)
Pour Point, °C (°F).....	-39 (-38.2)
Visual Color.....	Blue / Green
API Gravity.....	29.2

Typical values are listed. Variations not affecting the performance of this fluid may occur during production; however, these variations will not fall outside of set specification parameters.

Please consult AMALIE Technical Services or your local representative for a full listing of applications.

Technical Services:
(800) 368-1264
techservices@amalie.com

Always refer to your vehicles operating manual to select the correct grade of oil for your engine. The data presented herein are believed to be accurate; however, Amalie Oil Company shall not be liable for its content and makes no warranty with respect thereto.

PRO TWO-CYCLE TC-W3[®] RL Engine Oil

VISCOSITY	PACK SIZE	PART #
TC-W3 [®] RL	24-8 Ounce	160-62732-97
	12-1 Quart	160-62736-56
	4-1 Gallon	160-62737-36
	55 Gallon Drum	160-62733-05

Health and Safety

Safety Data Sheets (SDS) are available from your sales representative or at AMALIE.com.