

Better than it has to be[®] Since 1903

ROLLING OIL

GENERAL PURPOSE

BENEFITS:

- » Oxidation Resistance and Thermal Stability
- » Non-Staining Will Not Discolor Finishes
- » Superior Rust and Corrosion for Gears and Bearings
- » Rapid Water Separation
- » Quick Foam Release



ISO

15

MADE IN U.S.A.

MADE IN U.S.A.



ROLLING OIL GENERAL PURPOSE

AMALIE Rolling Oil – General Purpose 15 is a multipurpose rolling oil formulated from premium base stocks and using quality additives which are non-staining. This rolling oil provides wear, rust, and oxidation protection, and contain lubricity agents to improve the metal finish. **AMALIE Rolling Oil – General Purpose 15** is recommended for use in a variety of rolling applications for nonferrous materials, such as aluminum, copper, brass, and other copper alloys. This product is non-staining, does not contain zinc, and provides very good wear protection for use in hydraulic systems. It demonstrates exceptional oxidation resistance, foam control, rust and corrosion protection, and rapid demulsibility.

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

ISO Viscosity Grade	15
API Gravity	
Flash Point, °C	180
Viscosity @ 100°C, cSt	3.3
Viscosity @ 40°C, cSt	15
Viscosity Index	
Pour Point, °C	25

Typical values are listed. Variations not affecting the performance of this fluid may occur during production; however, these variations will not fall outside of set specification parameters.

Additional Information

Please use proper handling and care that you would use with any lubricating oil.

Please consult AMALIE Technical Services or your local representative for a full listing of applications. Technical Services: • (800) 368-1264 • techservices@amalie.com

ROLLING OIL GENERAL PURPOSE

VISCOSITY	PACK SIZE	PART #
15	55 Gallon Drum	160-67973-05

Health and Safety

Safety Data Sheets (SDS) are available from your sales representative or at AMALIE.com.

The data presented herein are believed to be accurate; however, Amalie Oil Company shall not be liable for its content and makes no warranty with respect thereto.